

Battery Chemistry Guide

Battery Chemistry Guide

Choosing the right battery chemistry for your deployment is critical. The wrong choice leads to shortened battery life, safety hazards, or a node that fails in cold weather.

Li-ion 18650 Cells

The 18650 is the workhorse battery for DIY LoRa nodes. Named for its dimensions (18mm × 65mm), it is widely available, well-understood, and supported by most mid-range device designs with a holder.

Warning: Most 18650 cells sold on Amazon are counterfeit. The highest-capacity genuine 18650 cells on the market are roughly 3500mAh; anything advertised far above that (for example a 6000mAh cell from an unknown brand) is physically impossible and counterfeit. Buy from reputable electronics retailers only.

Recommended 18650 Cells

Prices below are approximate and volatile (as of 2026-06-08). Capacity and current ratings are from each manufacturer's datasheet.

Cell	Price	Capacity	Max Continuous	Notes
Samsung 35E Protected	\$10	3500mAh	8A	Good all-around; protected circuit prevents overdischarge. 8A continuous per Samsung SDI INR18650-35E datasheet
Molicel M35A Protected	\$12	3450mAh typ (3500mAh rated)	10A	Slightly higher max current than Samsung 35E (per Molicel datasheet)

Cell	Price	Capacity	Max Continuous	Notes
Panasonic NCR18650GA	\$14	3450mAh	10A	Excellent quality; established brand (3450mAh / 10A per Panasonic NCR18650GA datasheet)

All three options are equivalent for LoRa node use. Typical node average draw is <200 mA; brief TX bursts can reach several hundred mA momentarily but still far below the cells' 8 - 10A ratings, so any of these cells will work well. Buy protected cells - the protection circuit prevents over-discharge which can damage the cell - unless the device or holder already provides over-discharge protection (for example a DW01-based module), in which case unprotected cells are fine and fit holders better.

21700 Cells

21700 cells are slightly larger (21mm × 70mm) and offer higher capacity. Fewer devices have 21700 holders but they can be used in custom builds or with adapter sleeves.

Cell	Price	Capacity	Max Continuous
Samsung 50S	\$8 (as of 2026-06-08)	5000mAh	25A
Molicel P50B	\$11 (as of 2026-06-08)	5000mAh	45A continuous (60A max)

LiPo Packs

Lithium polymer packs in various capacities with JST connectors are the standard battery choice for devices without 18650 holders (Heltec V3, many LilyGo boards). Match the connector type carefully.

Pack	Price	Capacity	Connector	Fits
3000mAh JST SH 1.25	\$11	3000mAh	JST SH 1.25mm	Heltec V3, V4 (verify LilyGo board connector separately)
3200mAh JST	\$15	3200mAh	JST (verify pin count against RAKwireless datasheet)	RAK19026
Rokland LiPo Packs	\$10 - \$20	Multiple sizes	Micro JST 1.25	Various; check listing for exact connector

LiPo caution: LiPo cells can swell, catch fire, or vent if overcharged, over-discharged, punctured, or charged at low temperatures. Use only with a proper charge controller. Never charge below 0°C

- this 0°C charge floor applies to every lithium chemistry, including LiFePO4. For unattended outdoor deployments in cold climates, prefer Li-ion 18650 or LiFePO4 over LiPo, and use a BMS with a low-temperature charge cutoff regardless of chemistry.

LiFePO4 (Lithium Iron Phosphate)

LiFePO4 is strongly preferred for outdoor and cold-weather deployments. Key advantages over Li-ion/LiPo:

- **Temperature tolerance:** Discharges at much lower temperatures (down to ~ - 20°C). Like all lithium chemistries, it must NOT be charged below 0°C - charging below freezing causes lithium plating, permanent capacity loss, and a hidden internal-short fire risk. For cold climates use a BMS with low-temperature charge cutoff or a charge controller with a battery temperature sensor.
- **Safety:** Much less prone to thermal runaway and far more abuse-tolerant than LiPo/NMC, but not fireproof - severe overcharge or puncture can still cause a fire. Still use a BMS and proper fusing.
- **Cycle life:** 2000 - 4000 cycles vs. 300 - 1000 for standard Li-ion (cycle life varies widely with depth of discharge)
- **Discharge curve:** Flat 3.2V nominal vs. 3.7V for Li-ion - verify your device supports 3.2V operation

Trade-off: Lower energy density than Li-ion. A LiFePO4 pack of the same physical size will have less capacity than a Li-ion pack. At - 40°C (which equals - 40°F) plan for roughly 40 - 60% capacity loss even with LiFePO4 - this loss is temporary and recovers as the cells warm - and size accordingly.

Battery Chemistry Comparison

Note: all lithium chemistries below share the same 0°C charge floor. The "Cold Weather" rating reflects discharge/survival performance and thermal stability, not a difference in charge temperature - LiPo's disadvantage is its lower thermal stability and the rarer availability of a low-temperature-cutoff BMS, not a different minimum charge temperature.

Chemistry	Nominal Voltage	Cold Weather	Safety	Cycle Life	Best For
LiPo	3.7V	Poor	Moderate	300 - 500	Indoor, portable, attended deployments
Li-ion 18650	3.7V	Moderate	Good (protected)	500 - 800	General purpose; most DIY builds

Chemistry	Nominal Voltage	Cold Weather	Safety	Cycle Life	Best For
LiFePO4	3.2V	Excellent	Excellent	2000 - 4000	Outdoor permanent, cold climate, unattended

Revision #3

Created 2026-05-03 03:13:08 UTC by Mesh America Admin

Updated 2026-06-08 22:52:12 UTC by Mesh America Admin